

## TECHNICAL SPECIFICATION

S.NO	PROPERTY	INTERNATIONAL STD. ISO 13006 EN 176 GROUP BLA	ROYALE TOUCH VITRIFIED VALUE	METHOD OF TESTING
1.	Deviation in Length	± 0.6%	± 0.1%	EN 98
2.	Deviation in Thickness	± 5.0%	± 5.0%	EN 98
3.	Straightness of Sides	± 0.5%	± 0.1%	EN 98
4.	Rectangularity	± 0.6%	± 0.2%	EN 98
5.	Surface Flatness	± 0.5%	± 0.2%	EN 98
6.	Water absorption*	< 0.5%	< 0.05%	EN 99
7.	Mohs hardness*	> 6	> 8	EN 101
8.	Flexural Straightness*	> 27 N/mm <sup>2</sup>	> 47 N/mm <sup>2</sup>	EN 100
9.	Abrasion resistance	> 204 mm <sup>2</sup>	> 144 mm <sup>2</sup>	EN 102
10.	Skid Resistance (Friction Coefficient)	> 0.4	> 0.6	ASTM C-1028
11.	Breaking Strength*	1113 N	2830 N	ASTM C-648
12.	Density (g/cc)	> 2	2.4	DIN 51082
13.	Frost Resistance	Frost proof	Frost proof	EN 202
14.	Chemical Resistance	No damage	No damage	EN 106
15.	Thermal Shock Resistance	No damage	No damage	EN 104
16.	Colour Resistance	No damage	No damage	DIN 51094
17.	Thermal Expansion	< 9 x 10 <sup>-6</sup>	< 6 x 10 <sup>-6</sup>	EN 103
18.	Stain Resistance	Resistant	Resistant	ISO 10545-14
19.	Moisture Expansion	Nil	Nil	ISO 10545-10
20.	Glossiness	-	Min. 65% - 70% reflection	Glossmeter

## PACKING DETAILS

SIZE	NORMAL THICKNESS	NO. OF TILES/BOX	COVERAGE AREA	WT. OF BOX
800 X 800 mm	10.3 mm (approx)	3 pcs.	1.92 sq. mt.	42 kgs. (approx.)
600 X 600 mm	9.2 mm ( approx)	4 pcs.	1.44 sq. mt.	29 kgs. (approx.)

## APPLICATION AREAS:



DISCLAIMER: We reserve the right to delete & amend either totally or partially, any of the colours, shapes, sizes, references and other technical specifications contained in this catalogue at any time. The colours shown of tiles in this catalogue are purely illustrative and limited to printing process. Please refer to actual sample before final selection. The details of colours, sizes, references should be verified for Typographical errors. SHADE & SIZE VARIATIONS are inherent characteristics of ceramics. NO COMPLAINT SHALL BE ENTERTAINED ON TILES ALREADY LAID/FIXED.



MARKETED BY: **APV Resources**,  
145, St.Mary's Road, Alwarpet, Chennai  
600018, Phone no: 044 45028222